FKUv 1612

Premium

Type of control	CICLI OTHE COTTLI OHOL
Temperature display	external digital
Fault: warning signal	audio and visual
Interface	
volt-free alarm contact	-
Shelves	4
Number of baskets	
Maximum number of baskets	
Shelf material	clear-coated wire
Shelf loading	60 kg
Height of adjustable legs	- mm
Castors/type of castors	-
Handle	-
Foot pedal opener	-
Self-closing door	yes
Insulation	55 - 55 mm
Defrost water drain	_
Refrigerant	R 600a
Gross/net weight	44/41 kg
Interior light	ceiling lightning, with seperate switch
EAN-Nr.	9005382130278

Total gross capacity

Climate rating

Cooling system

Temperature range Gastronorm

Door/lid material

Liner Material

Type of control

Housing material/colour

Defrosting

Exterior dimensions in mm (w/d/h)

Interior dimensions in mm (w/d/h)

Energy consumption in 24 h

141 litre

600/615/830

441/439/667

0,898 kWh

forced-air

automatic +1°C to +15°C

steel/white

Insulating glass door

moulded polystyrol

elctronic controller

ST



- 1 Model classification:
- **** freezer compartment with -18 °C or colder
- N +16°C to +32°C 3 Climate Ratings: SN +10°C to +32°C
- Fixed water connection and solenoid valve (needs to be plumbed in)

ST +16°C to +38°C

T +16°C to +43°C