## **FKvsl 5412**

## **Premium**



| Total gross capacity              | 544 litre                               |
|-----------------------------------|---|
| Exterior dimensions in mm (w/d/h) | 750/730/1640                            |
| Interior dimensions in mm (w/d/h) | 600/560/1452                            |
| Energy consumption in 24 h        | 1,364 kWh                               |
| Climate rating                    | SN-ST                                   |
| Cooling system                    | forced-air                              |
| Defrosting                        | automatic                               |
| Temperature range                 | 0°C to +15°C                            |
| Gastronorm                        |   |
| Door/lid material                 | steel/silver                            |
| Door/lid material                 | Insulating glass door                   |
| Liner Material                    | moulded polystyrol                      |
| Type of control                   | analgoue controls                       |
| Temperature display               | external digital                        |
| Fault: warning signal             |   |
| Interface                         |   |
| volt-free alarm contact           | -                                       |
| Shelves                           | 6                                       |
| Number of baskets                 |   |
| Maximum number of baskets         |   |
| Shelf material                    | clear-coated wire                       |
| Shelf loading                     | 60 kg                                   |
| Height of adjustable legs         | - mm                                    |
| Castors/type of castors           | -                                       |
| Handle                            | Ergonomic handle                        |
| Foot pedal opener                 | -                                       |
| Self-closing door                 | yes                                     |
| Insulation                        |   |
| Defrost water drain               | -                                       |
| Refrigerant                       | R 600a                                  |
| Gross/net weight                  | 100/94 kg                               |
| Interior light                    | ceiling lightning, with seperate switch |
| EAN-Nr.                           | 9005382092378                           |
|                                   |   |
|                                   |   |
|                                   |   |
|                                   |   |
|                                   |   |
|                                   |   |
|                                   |   |
|                                   |   |
|                                   |   |
|                                   |   |
|                                   |   |
|                                   |   |

- 1 Model classification: -
- 2 \*\*\*\* freezer compartment with -18 °C or colder
- 3 Climate Ratings: SN +10°C to +32°C N +16°C to +32°C
- 4 Fixed water connection and solenoid valve (needs to be plumbed in)

**ST** +16°C to +38°C

**T** +16°C to +43°C